

	2020 HONDA PIONEER 700 SPECIFICATIONS			
Model	Pioneer 700-4 Deluxe (SXS700M4D)	Pioneer 700 Deluxe (SXS700M2D)	Pioneer 700-4 (SXS700M4)	Pioneer 700 (SXS700M2)
ENGINE				
Type	675cc liquid-cooled longitudinally mounted single-cylinder four-stroke			
Valve Train	OHV, two valves			
Bore x Stroke	102.0mm x 82.6mm			
Compression Ratio	9.2:1			
Induction	Fuel injection (PGM-FI), 40mm throttle body			
Ignition	Full Transistorized			
Starter	Electric			
Driveline	Direct front and rear driveshafts			
Transmission	Automotive-style w/ hydraulic torque converter, three speeds + reverse; three drive modes incl. 2WD, 4WD, 4WD w/ differential lock			
Clutch	Automatic			
SUSPENSION				
Front	Independent double wishbone; 7.9 in. travel			
Rear	Independent double wishbone; 9.1 in. travel			
BRAKES				
Front	Dual hydraulic calipers w/ 200mm discs			
Rear	Single hydraulic caliper w/ 170mm disc			
TIRES				
Front	25 x 8-12			
Rear	25 x 10-12			
MEASUREMENTS				
Length	114.7 in.			
Width	59.7 in.			
Height	78.5 in.	77.6 in.	78.5 in.	77.6 in.
Seat Height	34.2 in.			
Ground Clearance	10.7 in.			
Wheelbase	76.8 in.			
Turning Radius	14.8 ft.			
Fuel Capacity	7.9 gal. incl. 1.2 gal. reserve			
Cargo Bed Capacity	1000 lbs.			
Towing Capacity	1,500 lbs.			
Curb Weight*	1,424 lbs. (1,429 lbs. CA)	1,270 lbs. (1,285 lbs. CA)	1,409 lbs. (1,413 lbs. CA)	1,265 lbs.
OTHER				
Colors	Honda Phantom Camo®, Pearl Red	Honda Phantom Camo, Matte Silver	Metallic Silver	Red, White

*Includes all standard equipment, required fluids and full tank of fuel—ready to ride
Meets current CARB and EPA off-road emissions standards
Recommended for riders 16 years of age and older