

(12) **United States Patent**
Nakamura et al.

(10) **Patent No.:** **US 10,202,151 B1**
(45) **Date of Patent:** **Feb. 12, 2019**

(54) **SIDE-BY-SIDE VEHICLE**

(71) Applicant: **KAWASAKI JUKOGYO KABUSHIKI KAISHA**, Kobe-shi, Hyogo (JP)

(72) Inventors: **Kenta Nakamura**, Kobe (JP); **Takashi Hisamura**, Akashi (JP); **Itsuo Takegami**, Kobe (JP)

(73) Assignee: **KAWASAKI JUKOGYO KABUSHIKI KAISHA**, Kobe-shi, Hyogo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/928,990**

(22) Filed: **Mar. 22, 2018**

(51) **Int. Cl.**
B62D 33/02 (2006.01)
B62D 33/023 (2006.01)
B62D 25/12 (2006.01)
B60K 5/02 (2006.01)
F02M 35/16 (2006.01)
B60R 16/04 (2006.01)
B60K 1/04 (2006.01)

(52) **U.S. Cl.**
CPC **B62D 25/12** (2013.01); **B60K 5/02** (2013.01); **B60R 16/04** (2013.01); **F02M 35/162** (2013.01); **B60K 2001/0416** (2013.01)

(58) **Field of Classification Search**
CPC B60N 2/36; B62D 33/02; B60P 3/423
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,287,769	B2 *	10/2007	Thiemke	B62D 21/11
					180/312
8,167,351	B2 *	5/2012	Plowman	B60N 2/305
					296/69
8,534,747	B2 *	9/2013	Thurmon	B60N 2/24
					296/182.1
8,613,336	B2	12/2013	Deckard et al.		
9,211,924	B2 *	12/2015	Safranski	B60G 3/14
2004/0031639	A1 *	2/2004	Deves	B62D 33/03
					180/311
2004/0195018	A1 *	10/2004	Inui	B62D 3/12
					180/68.1
2004/0195019	A1 *	10/2004	Kato	B60K 13/02
					180/68.3
2004/0195034	A1 *	10/2004	Kato	B60K 17/34
					180/312
2004/0231900	A1 *	11/2004	Tanaka	B60K 13/02
					180/68.3



(Continued)

Primary Examiner — Bryan A Evans
(74) *Attorney, Agent, or Firm* — Alleman Hall Creasman & Tuttle LLP

(57) **ABSTRACT**

A cargo carrier having a depressed loading space includes a base carrier member, and a pair of right and left side carrier members disposed on right and left sides, respectively, of the base carrier member, and fastened to the pair of right and left rear frame members, respectively, from above. The base carrier member includes a bottom wall portion forming a bottom surface of the loading space, a front wall portion protruding upward from a front end of the bottom wall portion, and a pair of right and left side wall portions protruding upward from a right end and a left end, respectively, of the bottom wall portion. The pair of right and left side wall portions of the base carrier member are removably mountable on the pair of right and left side carrier members, respectively.

7 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0031694 A1* 2/2012 Deckard B60K 17/08
180/68.3
2016/0280145 A1* 9/2016 Vertanen B60P 3/40
2018/0170218 A1* 6/2018 Nowland B60N 2/80

* cited by examiner




Fig. 1




Fig. 2




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 10

SIDE-BY-SIDE VEHICLE

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a side-by-side vehicle including a cargo carrier.

Description of the Related Art

For example, U.S. Pat. No. 8,613,336 discloses a side-by-side vehicle of a four-wheel-drive type which travels off-road. This vehicle includes a riding space in which a driver seat and a passenger seat are provided, and which is surrounded by a cabin frame, a cargo carrier (cargo carrying portion) disposed rearward of the riding space, an engine, a CVT, and others which are disposed below the cargo carrier. An opening is provided in a portion of a floor portion (bottom wall portion) of the cargo carrier. This opening is closed by a detachable cover. In a case where maintenance for the engine, the CVT and others is performed, the cover is detached (removed) to allow a user to access the engine, the CVT and others through the opening provided in the floor portion of the cargo carrier.

However, in this configuration, a separation line formed between the cargo carrier and the cover is present in the floor portion (bottom wall portion) of the cargo carrier. Liquid such as rain water accumulated in a loading space of the cargo carrier flows into the separation line and then into a space in which the engine, the CVT, and others are disposed, through the separation line.

SUMMARY OF THE INVENTION

In view of the above-described circumstances, an object of the present invention is to allow a user to more easily perform a maintenance work for a driving power unit or the like disposed below a cargo carrier, and to prevent ingress of liquid from the cargo carrier into a space in which the driving power unit or the like is disposed.

According to an aspect of the present invention, a side-by-side vehicle comprises a vehicle body frame including a cabin frame section surrounding a riding space in which seats for a driver and a passenger are provided, and a pair of right and left rear frame sections disposed rearward of the cabin frame section; a driving power unit supported by the vehicle body frame; and a cargo carrier which is disposed above the driving power unit in a state in which the cargo carrier is supported by the vehicle body frame, and has a loading space with a depressed shape. The cargo carrier includes a base carrier member, and a pair of right and left side carrier members disposed on right and left sides, respectively, of the base carrier member and fastened to the pair of right and left rear frame sections, respectively, from above. The base carrier member includes a bottom wall portion forming a bottom surface of the loading space, a front wall portion protruding upward from a front end of the bottom wall portion, and a pair of right and left side wall portions protruding upward from a right end and a left end, respectively, of the bottom wall portion in such a manner that the pair of right and left side wall portions are lower than the front wall portion. The pair of right and left side wall portions of the base carrier member are removably mountable on the pair of right and left side carrier members, respectively.

In accordance with the above-described configuration, the cargo carrier has a separable structure, and a user can easily access the driving power unit or the like without excessively disassembling a vehicle body by detaching the base carrier member in a state in which the side carrier members are mounted on the rear frame sections, during maintenance. Since the base carrier member includes the bottom wall portion, the front wall portion, and the pair of right and left side wall portions, and a separation line of the cargo carrier is not formed on the bottom surface of the loading space, liquid accumulated in the loading space of the cargo carrier is not likely to reach the separation line. In addition, since a separation line between the base carrier member and each of the side carrier members is formed in a surface extending vertically rather than a horizontal surface, ingress of the liquid from an upper side into this separation line is not likely to occur. In this way, the maintenance work can be more easily performed because of the separable structure of the cargo carrier, and ingress of the liquid through the separation line into a space in which the driving power unit is disposed does not occur.

The above and further objects, features and advantages of the present invention will more fully be apparent from the following detailed description of preferred embodiment with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing a side-by-side vehicle (vehicle) according to one embodiment.

FIG. 2 is a perspective view showing a frame structure of the vehicle of FIG. 1.

FIG. 3 is a plan view showing the vehicle of FIG. 1, when viewed from above.

FIG. 4 is a perspective view showing a cargo carrier of the vehicle of FIG. 1.

FIG. 5 is a cross-sectional view showing a fastening portion at which a base carrier member and a side carrier member of the cargo carrier of FIG. 3 are fastened to each other, and a region which is in the vicinity of the fastening portion.

FIG. 6 is a cross-sectional view showing an engagement portion at which a front carrier member and a cross frame section are engaged with each other, and a region which is in the vicinity of the engagement portion, when viewed from the side (in a side view).

FIG. 7 is a cross-sectional view showing an engagement portion at which the front carrier member and the side carrier member are engaged with each other, and a region which is in the vicinity of the engagement portion when viewed from the rear (in a rear view).

FIG. 8 is a cross-sectional perspective view showing an engagement portion at which the front carrier member and the base carrier member are engaged with each other, and a region which is in the vicinity of the engagement portion, when viewed from the side (in a side view).

FIG. 9 is a plan view showing a state in which the front carrier member of the vehicle of FIG. 3 is detached.

FIG. 10 is a plan view showing a state in which the front carrier member and the base carrier member of the vehicle of FIG. 3 are detached.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, the embodiment of the present invention will be described with reference to the drawings.

FIG. 1 is a perspective view showing a side-by-side vehicle 1 (hereinafter will be simply referred to as the vehicle 1) according to one embodiment. FIG. 2 is a perspective view showing a frame structure of the vehicle 1 of FIG. 1. FIG. 3 is a plan view showing the vehicle 1 of FIG. 1, when viewed from above. Referring now to FIGS. 1 and 3, the vehicle 1 includes a pair of right and left front wheels 3 supported by (mounted on) the front portion of a vehicle body frame 2, and a pair of right and left rear wheels 4 supported by the rear portion of the vehicle body frame 2. A space formed between the right and left front wheels 3 is covered by a resin-made hood 5 from above. A pair of seats 6 (a driver seat and a passenger seat) are arranged side by side, at a location that is rearward of the hood 5, and is in the vicinity of the center of the vehicle body frame 2 in a forward and rearward direction.

As shown in FIGS. 1 to 3, the vehicle body frame 2 includes, for example, a cabin frame section 7, a pair of right and left rear frame sections 8, a cross frame section 9, and a pair of right and left rear gusset frame sections 10. The vehicle body frame 2 is a pipe frame including a plurality of pipe members coupled to each other. The cabin frame section 7 is disposed to surround a riding space S1 in which the seats 6 are provided. The pair of right and left rear frame sections 8 are disposed on right and left sides at a location that is rearward of the cabin frame section 7, and extend rearward. The cross frame section 9 is disposed rearward of the cabin frame section 7 and couples the front end portions of the pair of right and left rear frame sections 8 to each other. The pair of right and left rear gusset frame sections 10 couple the upper portions of the cabin frame section 7 to the rear portions of the pair of right and left rear frame sections 8, respectively.

Resin-made doors 11 are disposed on right and left sides of the seats 6 to allow a rider and a passenger to get into and out of the vehicle 1. A resin-made cargo carrier 12 is disposed behind the seats 6 and has a loading space S2 with a depressed (recessed) shape. A pair of right and left rear fenders 13 which are made of a resin are disposed on right and left sides of the cargo carrier 12 at a location that is above the rear wheels 4. The front ends of the rear fenders 13 are close to and face the rear ends of the doors 11, respectively. The outer surfaces of the rear fenders 13 in the vehicle width direction are coplanar with the outer surfaces of the doors 11 in the vehicle width direction, respectively.

The cargo carrier 12 includes a base carrier member 21, a pair of right and left side carrier members 22, and a front carrier member 23. In other words, the cargo carrier 12 has a separable structure including four members which are separably joined to each other. The base carrier member 21 mainly forms the bottom surface and front surface of the loading space S. The pair of right and left side carrier members 22 are disposed on right and left sides of the base carrier member 21 and mainly form the side surfaces of the loading space S2. The front carrier member 23 is disposed in front of the base carrier member 21 and mainly forms the upper portion of the front surface of the loading space S2.

The base carrier member 21 covers from above an engine (driving power unit) E and a continuously variable transmission (CVT) TM which are supported by (mounted on) the vehicle body frame 2. The side carrier members 22 cover the rear frame sections 8 from above and are fastened to the rear frame sections 8, respectively. Openings 22e are formed in the rear portions of the side carrier members 22, respectively, to expose the rear portions of the rear frame sections 8. The rear portions of the rear gusset frame sections 10 extend through the openings 22e of the side carrier members

22 and are fastened to the rear portions of the rear frame sections 8, respectively. A battery 14 and an air cleaner box 15 are disposed in front of the base carrier member 21. The battery 14 is an electric power supply for in-vehicle devices. The air cleaner box 15 serves to clean air (intake air) to be supplied to the engine E. The battery 14 and the air cleaner box 15 are arranged side by side in a rightward and leftward direction. The battery 14 and the air cleaner box 15 are covered by the front carrier member 23 from above. The side carrier members 22 extend in the forward and rearward direction from a location corresponding to the front end of the front carrier member 23 to a location corresponding to the rear end of the base carrier member 21.

FIG. 4 is a perspective view showing the cargo carrier 12 of the vehicle 1 of FIG. 1. As shown in FIG. 4, the cargo carrier 12 has the loading space S2 defined by the bottom surface, the front surface, the left side surface and the right side surface, by joining the base carrier member 21, the pair of right and left side carrier members 22, and the front carrier member 23 to each other. The loading space S2 opens upward and rearward. The base carrier member 21, the pair of right and left side carrier members 22, and the front carrier member 23 are fastened to the vehicle body frame 2 (or brackets mounted on the vehicle body frame 2) by fastening members 32 to 34 such as rivets.

The base carrier member 21 includes a bottom wall portion 21a, a front wall portion 21b, and a pair of right and left side wall portions 21c. The bottom wall portion 21a is the bottom surface of the loading space S2. The bottom wall portion 21a has a concave/convex structure including a depressed (recessed) region 30, and a plurality of convex (protruding) portions 31 protruding from the depressed region 30 in such a manner that the plurality of convex portions 31 are spaced apart from each other. This concave/convex structure is provided in most of the bottom wall portion 21a including a center. The front wall portion 21b protrudes upward from the front end of the bottom wall portion 21a. When viewed from above (in a plan view) (see FIG. 3), the front wall portion 21b has a shape in which it protrudes forward, as a whole. More specifically, when viewed from above, the front wall portion 21b has a substantially circular-arc shape. The pair of right and left side wall portions 21c protrude upward from the right end and left end, respectively, of the bottom wall portion 21a. The upper ends of the pair of right and left side wall portions 21c are lower than the upper end of the front wall portion 21b. The height of the pair of right and left side wall portions 21c is, for example, 5 to 50%, preferably, 10 to 30% of the height of the front wall portion 21b. The front ends of the pair of right and left side wall portions 21c are connected to the lower portion of the front wall portion 21b.

Each of the pair of right and left side carrier members 22 includes a side wall portion 22a, an upper wall portion 22b, an outer end wall portion 22c, and a rear wall portion 22d. The lower end portion of each of the side wall portions 22a is connected to the upper end portion of the side wall portion 21c of the base carrier member 21 and forms the side surface of the loading space S2. The upper wall portion 22b protrudes outward in the vehicle width direction (rightward and leftward direction) from the upper end of the side wall portion 22a. The upper surface of the upper wall portion 22b is a horizontal surface. The outer end wall portion 22c protrudes upward from the outer end of the upper wall portion 22b in the vehicle width direction. The upper end of the outer end wall portion 22c is connected to the rear fender 13. The rear wall portion 22d is connected to the rear end of the side wall portion 22a and the rear end of the upper wall

5

portion **22b**. Each of the pair of right and left side carrier members **22** (the upper wall portion **22b** and/or the rear wall portion **22d**) is formed with an opening **22e** for allowing the rear portion of the rear gusset frame section **10** (see FIG. 1) to be coupled to the rear portion of the rear frame section **8**.

The front carrier member **23** includes an upper wall portion **23a**, a rear wall portion **23b**, a front wall portion **23c**, and a pair of right and left side wall portions **23d**. The front carrier member **23** extends in the rightward and leftward direction, from a location corresponding to the left end of the base carrier member **21** to a location corresponding to the right end of the base carrier member **21**, on a front side of the base carrier member **21**. The upper wall portion **23a** is disposed above the battery **14** and the air cleaner box **15**. The upper end of the air cleaner box **15** is higher than the upper end of the battery **14**. In this structure, a region (namely, right section **23aa**) of the upper wall portion **23a** which is right (immediately) above the air cleaner box **15** is higher than a region (left section **23ab**) of the upper wall portion **23a** which is right above the battery **14**.

The rear wall portion **23b** of the front carrier member **23** protrudes downward from the rear end of the upper wall portion **23a**. When viewed from above (in a plan view), the rear wall portion **23b** has a shape in which it protrudes forward, as a whole. Specifically, when viewed from above, the rear wall portion **23b** has a substantially circular-arc shape. The rear wall portion **23b** of the front carrier member **23** is coplanar (flush) with the front wall portion **21b** of the base carrier member **21**, and is connected to the upper end portion of the front wall portion **21b** of the base carrier member **21**. In this structure, the rear wall portion **23b** of the front carrier member **23** and the front wall portion **21b** of the base carrier member **21** define the front surface of the loading space **S2**. The front wall portion **23c** of the front carrier member **23** protrudes downward from the front end of the upper wall portion **23a** (see FIG. 6). The pair of right and left side wall portions **23d** protrude downward from the right end and left end, respectively, of the upper wall portion **23a**, and are connected to the rear wall portion **23b** and the front wall portion **23c**. The rear surface of the air cleaner box **15** has a shape (e.g., circular-arc shape) conforming to that of the rear wall portion **23b** of the front carrier member **23**.

FIG. 5 is a cross-sectional view showing a fastening portion at which the base carrier member **21** and the side carrier member **22** of the cargo carrier of FIG. 3 are fastened to each other, and a region which is in the vicinity of the fastening portion. As shown in FIG. 5, each of the pair of right and left side wall portions **21c** of the base carrier member **21** is removably fastened to the side wall portion **22a** of the side carrier member **22** by a fastening member **24** such as a rivet, in a state in which the side wall portion **21c** is lapped on the side wall portion **22c** from the loading space **S2** side. The lower end portion of the side wall portion **22a** of the side carrier member **22** is formed with a stepped portion **22aa** protruding toward the loading space **S2**. The upper end portion of the side wall portion **21c** of the base carrier member **21** is formed with a curved portion **21ca** protruding away from the loading space **S2** in such a manner that the curved portion **21ca** conforms in shape to the stepped portion **22aa**. In this structure, the base carrier member **21** can be easily aligned with each of the side carrier members **22**. In addition, the base carrier member **21** can be easily dismounted (detached) from each of the side carrier members **22**.

As described above, the bottom wall portion **21a** of the base carrier member **21** has the concave/convex structure. The depressed region **30** of the bottom wall portion **21a** is

6

formed with a drain hole **H** at a location that is apart from the engine **E** in the rightward and leftward direction, in a plan view. In the present embodiment, the drain hole **H** is provided at a location that is in front of and lateral of the engine **E** (rightward or leftward of the engine **E**) in a plan view. The bottom surface **30a** of the depressed region **30** is an inclined surface which is slightly inclined toward the drain hole **H**. In contrast, the upper surfaces **31a** of the plurality of convex portions **31** are horizontal surfaces arranged on the same plane. Therefore, the bottom surface **30a** of the depressed region **30** and the upper surfaces **31a** of the convex portions **31** are not parallel to each other. Although the depressed region **30** is apparently partitioned by the convex portions **31**, in the example of FIG. 5, the plurality of convex portions **31** are actually arranged like lands, and thus the depressed region **30** has a labyrinth structure as shown in FIG. 4.

FIG. 6 is a cross-sectional view showing an engagement portion at which the front carrier member **23** and the cross frame section **9** are engaged with each other, and a region which is in the vicinity of the engagement portion, when viewed from the side (in a side view). FIG. 7 is a cross-sectional view showing an engagement portion at which the front carrier member **23** and the side carrier member **22** are engaged with each other, and a region which is in the vicinity of the engagement portion, when viewed from the rear (in a rear view). FIG. 8 is a cross-sectional perspective view showing an engagement portion at which the front carrier member **23** and the base carrier member **21** are engaged with each other, and a region which is in the vicinity of the engagement portion, when viewed from the side. As shown in FIG. 6, the cross frame section **9** is a rectangular pipe, and an upper plate portion **9a** of the cross frame section **9** is formed with a slit **9b** (engaged portion). The slit **9b** is located at a distance from the front end of the upper plate portion **9a**.

An engagement portion **23ca** protruding forward is formed in the lower end portion of the front wall portion **23c** of the front carrier member **23**. In a case where the front carrier member **23** is mounted on the cross frame section **9**, the front carrier member **23** is tilted forward, then the engagement portion **23ca** of the front carrier member **23** is inserted into the slit **9b** of the cross frame section **9** (see two-dotted line of FIG. 6), and then the front carrier member **23** is tilted backward (rearward). In this way, the engagement portion **23ca** of the front carrier member **23** is engaged with the cross frame section **9** while preventing the engagement portion **23ca** from being disengaged from the slit **9b**.

As shown in FIG. 7, a slit **22ba** is formed in a portion of the upper wall portion **22b** of the side carrier member **22**, the portion corresponding to the side wall portion **23d** of the front carrier member **23**. An engagement portion **23da** protruding downward is formed in the lower end portion of the side wall portion **23d** of the front carrier member **23**. This engagement portion **23da** is inserted into the slit **22ba** of the side carrier member **22**, and thus the front carrier member **23** is positioned with respect to each of the side carrier members **22**.

As shown in FIG. 8, a groove **21ba** which opens upward is formed in the upper end portion of the front wall portion **21b** of the base carrier member **21**. A tapered engagement portion **23ba** with a dimension reduced in the downward direction protrudes downward from the lower end portion of the rear wall portion **23b** of the front carrier member **23**. This engagement portion **23ba** is inserted into the groove **21ba** from above, and thus the front carrier member **23** is positioned with respect to the base carrier member **21**. An

engaged hole **21bb** is formed on the bottom surface of the groove **21ba**. The tapered engagement portion **23ba** protruding downward from the lower end portion of the rear wall portion **23b** of the front carrier member **23** is inserted into the engaged hole **21bb**. In this way, the front carrier member **23** is precisely positioned with respect to the base carrier member **21**. In this state, the rear surface of the rear wall portion **23b** of the front carrier member **23** and the rear surface of the front wall portion **21b** of the base carrier member **21** are coplanar with each other.

In the above-described manner, the front carrier member **23** is engaged with the cross frame section **9**, the base carrier member **21**, and the side carrier members **22**. Portions of the front carrier member **23** which are close to the vehicle body frame **2** are fastened to the vehicle body frame **2** (or the brackets fastened to the vehicle body frame **2**) by fastening members **34**. Portions of the base carrier member **21** which are close to the vehicle body frame **2** are fastened to the vehicle body frame **2** (or the brackets fastened to the vehicle body frame **2**) by fastening members **32**.

Next, a maintenance work performed for the vehicle **1** will be described. FIG. **9** is a plan view showing a state in which the front carrier member **23** of the vehicle **1** of FIG. **3** is detached. As shown in FIG. **9**, by detaching the front carrier member **23**, the battery **14** and the air cleaner box **15** are exposed. In this state, change (exchange) of the battery **14**, change of a filter element of the air cleaner box **15**, connection of accessory members to the terminals of the battery **14**, or the like can be performed. In other words, by merely detaching the front carrier member **23**, a user can access the battery **14** and the air cleaner box **15** without disassembling the whole of the cargo carrier **12**. The user can perform the maintenance work for the battery **14** or the air cleaner box **15** in a state in which the user gets on the base carrier member **21**.

FIG. **10** is a plan view showing a state in which the front carrier member **23** and the base carrier member **21** of the vehicle **1** of FIG. **9** are detached. As shown in FIG. **10**, by detaching the base carrier member **21** after the front carrier member **23** is detached, the engine **E** and the CVT **TM** are exposed. In this state, change (exchange) of a belt of the CVT **TM**, adjustment of a valve inside a cylinder head cover of the engine **E**, or the like can be performed. In brief, by detaching the front carrier member **23** and the base carrier member **21** in a state in which the right and left side carrier members **22** are mounted on the right and left rear frame sections **8**, respectively, the user can easily access the engine **E** and the CVT **TM** without a need to excessively perform a disassembling (dismounting) work.

In the vehicle **1** in which strength of the vehicle body frame **2** is increased by use of the rear gusset frame sections **10**, it is necessary to dismount the rear gusset frame sections **10** if the side carrier members **22** should be detached. However, during the maintenance work, it is not necessary to detach the side carrier members **22**. As a result, strength of the frame can be increased and the maintenance work can be easily performed.

The base carrier member **21** includes the bottom wall portion **21a**, the front wall portion **21b**, and the pair of right and left side wall portions **21c**, and a separation line of the cargo carrier **12** is not formed in the bottom surface of the loading space **S2**. In this structure, liquid accumulated in the loading space **S2** of the cargo carrier **12** does not easily reach the separation line. A separation line formed between the base carrier member **21** and the side carrier member **22** is formed in the side surface extending vertically rather than a horizontal surface. In this structure, ingress of the liquid into

the separation line due to a hydraulic head pressure is not likely to occur. Therefore, the maintenance work can be more easily performed because of the separable structure of the cargo carrier **12**, and it becomes possible to prevent ingress of the liquid through the separation line into the space in which the engine **E** is disposed.

Each of the pair of right and left side wall portions **21c** of the base carrier member **21** is fastened to the side wall portion **22a** of corresponding one of the side carrier members **22** in a state in which the side wall portion **21c** is lapped on the side wall portion **22a** from the loading space **S2** side. Therefore, the base carrier member **21** can be easily detached from the loading space **S2** side while maintaining a state in which the side carrier members **22** are fastened to the vehicle body frame **2**.

The rear wall portion **23b** of the front carrier member **23** is mounted on the front wall portion **21b** of the base carrier member **21**, the pair of right and left side wall portions **23d** of the front carrier member **23** are mounted on the pair of right and left side carrier members **22**, respectively, and the separation line of the cargo carrier **12** is not formed in the wall (the upper wall portion **23a** of the front carrier member **23**) of the cargo carrier **12** which is located above the battery **14** and the air cleaner box **15**. In this structure, it becomes possible to prevent a situation in which the liquid accumulated in the upper surface of the front carrier member **23** flows through the separation line into the space in which the battery **14** and the air cleaner box **15** are disposed. Further, since the separation line between the rear wall portion **23b** of the front carrier member **23** and the front wall portion **21b** of the base carrier member **21** is formed in the surface extending vertically, ingress of the liquid into this separation line due to the hydraulic head pressure is not likely to occur. In this way, ingress of the liquid through the separation line into the space does not occur.

Since the engagement portion **23ca** provided in the front wall portion **23c** of the front carrier member **23** is engaged with the cross frame section **9**, the front carrier member **23** can be stably supported by the vehicle body frame **2**, the front carrier member **23** can be easily removably (detachably) mounted, and the maintenance for the battery **14** and the air cleaner box **15** can be easily performed.

The upper surfaces **31a** of the plurality of convex portions **31** of the bottom wall portion **21a** of the base carrier member **21** are horizontal surfaces which are on the same plane, and the bottom surface **30a** of the depressed (recessed) region **30** of the bottom wall portion **21a** of the base carrier member **21** is the inclined surface inclined toward the drain hole **H**. In this structure, stuff (e.g., spare tire) loaded in the loading space **S** can be horizontally supported on the upper surfaces **31a** of the plurality of convex portions **31** in the concave/convex structure of the bottom wall portion **21a** of the base carrier member **21**, and the liquid accumulated in the depressed region **30** can be smoothly discharged through the drain hole **H**.

The front surface (the front wall portion **21b** and the rear wall portion **23b**) of the loading space **S2** of the cargo carrier **12** has a shape (circular-arc shape) in which it protrudes forward as a whole. Because of this shape, the battery **14** and the air cleaner box **15** can be disposed in front of the loading space **S2**, and the spare tire and the like of the vehicle **1** can be disposed in the loading space **S2**. In this way, high space efficiency can be realized.

Numerous modifications and alternative embodiments of the present invention will be apparent to those skilled in the art in view of the foregoing description. Accordingly, the description is to be construed as illustrative only, and is

provided for the purpose of teaching those skilled in the art the best mode of conveying out the invention. The details of the structure and/or function may be varied substantially without departing from the spirit of the invention. For example, although the cargo carrier **12** includes the four members which are separable from each other, the cargo carrier **12** may include five or more members which are separable from each other. Further, although the vehicle **1** includes the engine **E** which is an internal combustion engine as the driving power unit which generates the driving power for allowing the vehicle **1** to travel, the vehicle **1** may include an electric motor instead of the engine **E**.

The invention claimed is:

1. A side-by-side vehicle comprising:

a vehicle body frame including a cabin frame section surrounding a riding space in which seats for a driver and a passenger are provided, and a pair of right and left rear frame sections disposed rearward of the cabin frame section;

a driving power unit supported by the vehicle body frame; and

a cargo carrier which is disposed above the driving power unit in a state in which the cargo carrier is supported by the vehicle body frame, and has a loading space with a depressed shape,

wherein the cargo carrier includes a base carrier member, and a pair of right and left side carrier members disposed on right and left sides, respectively, of the base carrier member and fastened to the pair of right and left rear frame sections, respectively, from above,

wherein the base carrier member includes a bottom wall portion forming a bottom surface of the loading space, a front wall portion protruding upward from a front end of the bottom wall portion, and a pair of right and left side wall portions protruding upward from a right end and a left end, respectively, of the bottom wall portion, and

wherein the pair of right and left side wall portions of the base carrier member are removably mountable on the pair of right and left side carrier members, respectively.

2. The side-by-side vehicle according to claim **1**,

wherein the pair of right and left side wall portions of the base carrier member are removably fastened to the pair of right and left side wall portions of the pair of right and left side carrier members, respectively, in a state in which the pair of right and left side wall portions of the base carrier member are lapped on the pair of right and left side wall portions of the pair of right and left side carrier members, respectively, from the loading space side.

3. The side-by-side vehicle according to claim **1**,

wherein the pair of right and left side carrier members include a pair of right and left side wall portions, respectively, forming side surfaces of the loading space,

wherein upper ends of the pair of right and left side wall portions of the base carrier member are lower than an upper end of the front wall portion of the base carrier member, and

wherein the pair of right and left side wall portions of the base carrier member are removably mountable on the pair of right and left side wall portions of the pair of right and left side carrier members, respectively.

4. The side-by-side vehicle according to claim **1**, further comprising:

a battery and an air cleaner box which are disposed in front of the base carrier member,

wherein the cargo carrier further includes a front carrier member covering the battery and the air cleaner box from above,

wherein the front carrier member includes an upper wall portion disposed above the battery and the air cleaner box, a rear wall portion protruding downward from a rear end of the upper wall portion and forming a front surface of the loading space, and a pair of right and left side wall portions protruding downward from a right end and a left end, respectively, of the upper wall portion,

wherein the rear wall portion of the front carrier member is removably mountable on the front wall portion of the base carrier member, and

wherein the pair of right and left side wall portions of the front carrier member are removably mountable on the pair of right and left side carrier members, respectively.

5. The side-by-side vehicle according to claim **4**, further comprising:

wherein the vehicle body frame includes a cross frame section disposed rearward of the cabin frame section and connecting front end portions of the pair of right and left rear frame sections to each other,

wherein the front carrier member further includes a front wall portion protruding downward from a front end of the upper wall portion, and

wherein the front wall portion of the front carrier member includes an engagement portion which is engageable with an engaged portion formed in the cross frame section.

6. The side-by-side vehicle according to claim **1**,

wherein the bottom wall portion of the base carrier member includes a depressed region formed with a drain hole, and a plurality of convex portions protruding upward from the depressed region in such a manner that the plurality of convex portions are spaced apart from each other,

wherein upper surfaces of the plurality of convex portions are horizontal surfaces, respectively, which are on a same plane, and

wherein a bottom surface of the depressed region is an inclined surface which is inclined toward the drain hole.

7. The side-by-side vehicle according to claim **1**,

wherein the vehicle body frame further includes a pair of right and left rear gusset frame sections coupling upper portions of the cabin frame section to rear portions of the pair of right and left rear frame sections, respectively,

wherein the pair of right and left side carrier members have openings, respectively, to expose the rear portions of the pair of right and left rear frame sections, and

wherein the pair of right and left rear gusset frame sections are fastened to the rear portions of the pair of right and left rear frame sections, respectively, through the openings of the pair of right and left side carrier members.

* * * * *