



2016 PIONEER 1000 SPECIFICATIONS*

ENGINE

Engine Type	999cc liquid-cooled twin-cylinder Unicam® four-stroke
Bore And Stroke	92.0mm x 75.1mm
Compression Ratio	10:1
Induction	Fuel Injection (PGM-FI), 44mm throttle body
Ignition	Full-transistorized with electronic advance

DRIVE TRAIN

Transmission	Fully-Automatic Dual Clutch Transmission (DCT) with six forward gears and Reverse. Four drive modes include 2WD, 4WD, Turf and Differential lock.
Driveline	Direct front and rear driveshafts

CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone; 10.55 inches travel
Rear Suspension	Independent double-wishbone; 10 inches travel
Front Brake	210mm hydraulic disc
Rear Brake	210mm hydraulic disc
Front Tires	27 x 9-12
Rear Tires	27 x 11-12

DIMENSIONS

Bed Capacity	1000 pounds
Towing Capacity	2000 pounds

OTHER

Note	Recommended for Drivers 16 years of age and older.
Available Colors	Red, Olive
Model Id	SXS1000M3

FACTORY WARRANTY INFORMATION

Duration	One Year
Description	Transferable limited warranty; extended coverage available with a Honda Protection Plan